

File E69654
Project 03CA06228
March 31, 2003

REPORT

on

WIRE CONNECTORS AND SOLDERING LUGS

Wago Kontakttechnik GmbH
Minden, Germany

Copyright © 2003 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

DESCRIPTION

PRODUCT COVERED:

USL, CNL Listed Splicing Wire Connectors, Cat. No. 222 followed by -41 thru -45 followed by 2, 3 or 5.

GENERAL CHARACTER AND USE:

The devices described in this Report are of the following type.

Type of Wiring Termination - Spring action.

The insulating cover described in this Report are molded from a Recognized Component plastic (QMFZ2), in two pieces and provided with Operating Leaver, intended to be used with this manufacturer's Listed connectors.

RATINGS:

Wire Range:

Series	Wire Range, AWG	Wire Type
222	28-12	SOL/STR, Cu

Insulation Temperature - 105°C.

Wire strip length - 9.0 mm.

Voltage - 600 V maximum.

Ampere Rating - 20 A.

*

NOMENCLATURE:

<u>222</u>	<u>-41</u>	<u>3</u>
A	B	C

A. Basic Type - Series 222

B. Model Color -
-41 - Gray
-42 - Blue
-43 - White
-44 - Red
-45 - BlackC. Number of Poles
2 - Poles
3 - Poles
5 - Poles